



	Hard-Wearing Carpet Roll width 200 cm, Roll length approx. 30 lfm.	Hard-Wearing Carpet Tiles Tile size 50 x 50 cm
Technical specification:		
Fibre composition of top surface:	88 % Polyamide 12 % Polypropylene Dorix-Fasern	35 % Polyamide 40 % Polypropylene 25 % Polyester Dorix-Fasern
Total fibre weight of top surface:	approx. 700 g/m ²	approx. 600 g/m ²
Backing:	Synthetic fleece	Heavy coating with non-woven cover
Total weight:	approx. 1,500 g/m ²	approx. 4,700 g/m ²
Total thickness as per DIN EN 1470:	approx. 6.5 mm	approx. 7.5 mm
Level of use:	Commercial 33	Commercial 33
Luxury rating:	LC 1	LC 1
Antistatic as per DIN 66095, part 4:	yes	yes
Body voltage walking test as per DIN EN 1470:	< 2.0 kV	< 2.0 kV
Vertical resistance as per DIN EN 1470:	R ^{DF} < 1x10 ⁷ Ohm	-
Resistance to earth as per DIN EN 1470:	R ^{EF} < 1x10 ⁷ Ohm (Completely stuck using conductive adhesive.)	-
Chair castor suitability as per DIN EN 1470:	yes	yes (with gluing or adhesive contact only)
Moisture proof suitability as per DIN EN 1470:	-	-
Floor heating suitability as per DIN EN 1470:	yes	yes
Thermal resistance as per DIN EN 1470:	0.12 m ² K/W	0.10 m ² K/W
Crocking resistance as per DIN EN 1470:	dry 5; wet 5	dry 4-5; wet 4-5
Water fastness as per DIN EN 1470:	Colour change 5	Colour change 5
Light fastness as per DIN EN 1470:	> 5	> 5
Impact sound improvement rate as per DIN EN 1470:	21 dB	21 dB
<u>Burning behaviour</u> as per DIN EN 13501-1:	C _{fl} -S ₁	C _{fl} -S ₁
CE label:	CE	CE 1658-CPD-1191
Emissions tested floor covering approved by DiBt (<i>Deutsches Institut für Bautechnik</i>):	Z-156.601-581 Filzfabrik Fulda GmbH & Co KG FFF 127 -02	Z-156.601-660 Filzfabrik Fulda GmbH & Co KG FFF 127 -02

