



17

LITHO GRADIENT ecoBack

| | | | |
|---|--|--|--|
| CONSTRUCTION STRUCTURE STRUKTUR STRUCTUUR | Tufted 1/12" Loop Tufté 1/12" Bouclé Getuftet 1/12" Schlinge Getuft 1/12" Luspool | FIRE RESISTANCE COMPORTEMENT AU FEU BRENNVERHALTEN BRANDGEDRAG | EN 13501-1 B _{fl} -s1 |
| PILE MATERIAL COUCHE D'USURE POLMATERIAAL POOLMATERIAAL | 100% ECONYL® yarn 100% regenerated solution dyed nylon | FASTNESS TO LIGHT SOLIDITÉ À LA LUMIÈRE LICHTECHTHEIT LICHTECHTHEID | ISO 105-B02 ≥ 7 |
| SECONDARY BACKING DOSSIER RÜCKENAUSSTATTUNG RUG | ecoBack: fully recyclable polyolefin based carpet tile backing with minimum 70% post-industrial recycled content | RUBBING FASTNESS SOLIDITÉ AU FROTTEMENT REIBECHTHEIT WRIJFECHTHEID | EN ISO 105-X12 ≥ 4 |
| TOTAL WEIGHT POIDS TOTAL GESAMTGEWICHT TOTAAL GEWICHT | Ca. 3.800 g/m ² Ca. 112,1 oz./yd ² | COLOUR FASTNESS TO WATER SOLIDITÉ À L'EAU WASSERRECHTHEIT WATERECHTHEID | EN ISO 105-E01 ≥ 4 |
| PILE WEIGHT POIDS DU VELOURS POLEINSATZGEWICHT POOLGEWICHT | Ca. 660 g/m ² Ca. 19,5 oz./yd ² | THERMAL RESISTANCE RÉSISTANCE THERMIQUE WÄRMEDURCHLABWIDERSTAND WÄRMEDOORLAATWEERSTAND | ISO 8302 0,077 m ² K/W |
| PILE ABOVE BACKING POIDS DE VELOURS UTILE POLNUTZSCHICHTGEWICHT NUTTIG POOLGEWICHT | Ca. 450 g/m ² Ca. 13,3 oz./yd ² | IMPACT NOISE RATING ISOLATION PHONIQUE TRITTSCHALLVERBESSERUNGMAß GELUIDSISOLATIE | ISO 10140 ΔL _w : ca 26 dB |
| TOTAL HEIGHT EPAISSEUR TOTALE GESAMTDICKE TOTALE DIKTE | Ca. 7,2 mm Ca. 0,28" | SOUND ABSORPTION ABSORPTION PHONIQUE SCHALLABSORPTIONSGRAD GELUIDSABSORPTIE | ISO 354 α _w : 0,20 |
| PILE HEIGHT EPAISSEUR DU VELOURS POLDICKE POOLHOOGTE | Ca. 3,5 mm Ca. 0,14" | PERMANENT ANTISTATIC ANTISTATIQUE PERMANENT PERMANENT ANTISTATISCH PERMANENT ANTISTATISCH | ISO 6356 ≤ 2 kV |
| PILE DENSITY DENSITÉ DU VELOURS POLROHDICHTHEIT POOLDICHTHEID | Ca. 0,129 g/cm ³ Ca. 3.479 oz./yd ³ | TRANSVERSAL RESISTANCE RÉSISTANCE TRANSVERSALE DURCHGANGSWIDERSTAND DOORGANGSWEERSTAND | ISO/DIS 10965 ≤ 1 x 10 ⁹ Ohm |
| TUFT DENSITY NOMBRE DE TOUFFES NOPPENZAHL AANTAL PUNTEN | Ca. 220.000 /m ² Ca. 183.946 /yd ² | SIZE & PACKING DIMENSION & EMBALLAGE ABMESSUNG & VERPAKKUNG AFMETINGEN & VERPAKKING | 50 cm x 50 cm box: 5m ² pallet: 20 boxes |
| CLASSIFICATION CLASSEMENT KLASSIFIKATION CLASSIFICATIE | EN 1307 33- LC2 | NUMBER OF COLOURS NOMBRE DE COLORIS ANZAHL DER FARBEN AANTAL KLEUREN | 16 |
| CASTOR CHAIR SUITABILITY EMPLOI CHAISE À ROULETTES STUHLROLLENEIGNUNG ROLSTOELGESCHIKTHEID | EN 985 A : continuous use | DIMENSIONAL STABILITY STABILITÉ DIMENSIONNELLE DIMENSIONSTABILITÄT DIMENSIONELE STABILITEIT | EN 986 max. 0,2 % |
| CRADLE TO CRADLE CERTIFIED™ | Gold level | GUT-NR | ACBF3E3E |
| | | LEED® | Product contributes toward satisfying Credits under LEED®.* |
| | | DGNB | modulys is member of DGNB, the German Sustainable Building Council. |

We reserve all rights for technical improvements. Technische wijzigingen behouden wij ons voor. Technische wijzigingen behouden wij ons voor. Technische wijzigingen behouden wij ons voor.

*For more information, see the modulys website page dedicated to "Green" Products and the LEED, LEED and LEED certification requirements on the website. For more information on the design, construction and operation of green buildings, for more information on LEED, visit www.usgbc.org/greenbuild.



modulys
Zevensterrestraat 21
B 9240 Zele
T +32 (0)52 80 80 80
F +32 (0)52 80 82 00
info@modulys.com
www.modulys.com