

# TECHNICAL INFORMATION - WOVEN VINYL FLOOR COVERINGS

		STANDARD	BE DIFFERENT	BE SMART	BE EASY	BE NATURAL
Use classification		EN 685	33 Heavy commercial	33 Heavy commercial	33 Heavy commercial	33 Heavy commercial
Fire classification		EN 13501-1	Cfl s1	Cfl s1	Cfl s1	Cfl s1
		ASTM E 648	1st Class	1st Class	1st Class	1st Class
Optical smoke density		ASTM E 662	<450	<450	<450	<450
Soundproofing		ISO 140-8	18dB	17dB	17dB	18dB
Roll width		EN 426	200 cm		200 cm	200 cm
Roll length			25 m		25 m	25 m
Tile size		EN 994		50 x 50 cm	50 x 50 cm	
				Box of 16 tiles / 4 sq.m.	Box of 16 tiles / 4 sq.m.	
Thickness		ISO 1765	4 mm	3,7 mm	3,7 mm	4 mm
Weight*		ISO 8543	3,1 kg/m <sup>2</sup>	3,15 kg/m <sup>2</sup>	3,15 kg/m <sup>2</sup>	3,1 kg/m <sup>2</sup>
Castor chair		EN 985	Continuous use	Continuous use	Continuous use	Continuous use
Body voltage		ISO 6356	< 2kv	< 2kv	< 2kv	< 2kv
Residual indentation		EN 433	<0,2	<0,2	<0,2	<0,2
Fraying		EN 1814	Frayproof	Frayproof	Frayproof	Frayproof
Thermal resistance		ISO 8302	Suitable for underfloor heating	Suitable for underfloor heating	Suitable for underfloor heating	Suitable for underfloor heating
Dimensional stability		ISO 2551 / EN 434	<0,1%	<0,1%	<0,1%	<0,1%
Colourfastness to light		ISO 105 B02	8/8	8/8	8/8	8/8
Colourfastness to weather		ISO 105 B04	8/8	8/8	8/8	8/8
Slip resistance		EN 13893	μ > 0,3	μ > 0,3	μ > 0,3	μ > 0,3
CE Certification		EN 14 041	0493-CPD-0101	0493-CPD-0101	0493-CPD-0101	0493-CPD-0101
Floorscore Certification (rolls + tiles)		SCS-EC10.2-2007	SCS - FS - 02719	SCS - FS - 02719	SCS - FS - 02719	SCS - FS - 02719
Oeko-Tex® Certification		Oeko-Tex 100 (IV)	CQ 638/5	CQ 638/5	CQ 638/5	CQ 638/5

\*+/- 5%

01/2013



10 rue des châteaux  
BP 109 - Z.I. la Pilaterie  
59443 Wasquehal Cedex - France  
www.dickson-constant.com  
Tél. + 33 (0)3 20 45 59 59  
Fax. + 33 (0)3 20 45 59 00

Performance fabrics for :  
solar protection  
outdoor furniture  
indoor furniture  
marine furnishing  
flooring

